

SoloSeries

Easy, economical industrial printers delivering the quality you expect at the price you want.

FoxJet offers the SoloSeries printer line that brings simplicity and ruggedness to the thermal jet printing technology.

Inkjet
Technology by



FoxJet SoloSeries

The SoloSeries thermal inkjet printers from FoxJet feature three controller options and many printing capabilities including up to 10 lines of alphanumeric as well as logos and barcodes. The enclosed printhead design of the SoloSeries printers makes them truly industrial.

- Porous or Non-Porous Printing
- Print Heights Ranging From 1/10" – 1"
- Optional Bulk Ink Supply
- Built-In Autocodes
- Includes PC Software

FOXJET[®]
AN ITW COMPANY

www.foxjet.com

SoloSeries 45

FoxJet's SoloSeries 45 printhead offers up to 5 lines of print, varying character heights and easy logo placement for simple and flexible message creation. Built-in autocodes such as date, time, count and expiration are easy to utilize. And the rugged enclosure protects the print cartridge, ensuring optimum print quality in industrial environments.

Lines of Print	Up to 5
Print Height	1/10" to 1/2"
Print Orientation	Side or top-down
Print Speed	Up to 200 fpm
Port	Serial RS-232
Resolution	300 DPI (vertical and horizontal)
Sensors	Internal photocell for product detection and speed, indicator lamp for ink level
Environment	50°F – 104°F (10°C – 40°C) 10-90% (non-condensing)
Ink*	Solo 100, Solo 200 porous substrates Solo 300 non-porous substrates


*Must use FJ branded ink for full functionality of the system

SoloSeries 90

The SoloSeries 90 printhead from FoxJet offers up to a 1" tall print area for alphanumeric, logos and barcodes with NO MANUAL STITCHING. The SoloSeries 90 features two sets of photo sensors to ensure your message prints perfectly each time. And the printer's robust build with its stainless steel faceplate provides durability and longevity.

Lines of Print	Up to 10
Print Height	1/10" to 1"
Print Orientation	Side or top-down
Print Speed	Up to 200 fpm
Port	Serial RS-232
Resolution	300 DPI (vertical and horizontal)
Sensors	Internal photocell for product detection and speed, indicator lamp for ink level
Environment	50°F – 104°F (10°C – 40°C) 10-90% (non-condensing)
Ink*	Solo 100, Solo 200 porous substrates Solo 300 non-porous substrates

*Must use FJ branded ink for full functionality of the system





Marksman HHI

FoxJet's Solo HHI controller offers a simple solution for controlling a daisy chain of printheads without the use of a PC. The handheld can control up to 16 printheads in two daisy chains and allows the user easy access to change the message.

Display	7" Color LCD Touch Screen
Message Storage	128MB flash memory
Keyboard	Sealed Elastomeric QWERTY
Printhead Capability	Up to 16 SoloSeries 45 or 8 SoloSeries 90
Printhead Interface	RS-232
Communication Ports	USB-port, RS-232-2 port, 100 base - T Ethernet
Barcodes Supported	GTIN-12 (UPC-A), UPC-E, GTIN-13 (EAN-13), GTIN-8 (EAN-8), Code 39, GTIN-14 (UCC-128), Code 128, Data Matrix
Environment	Ambient operating temperature - 40° to 104° (5°C to 40°C), Operating Humidity 10%-90%, non-condensing



Marksman Duo IPC

FoxJet's Marksman Duo controller is designed to give the user the same intuitive interface that PC software offers. The Marksman Duo controller can control up to 16 printheads in two daisy chains allowing maximum efficiency in message changeover. This controller's impressive amount of memory gives you the ability to store an unlimited number of messages.

Enclosure	Painted Steel
Display	5.7", 320x240, Color LCD, Touch Screen
Message Storage	16MB Flash Memory
Keyboard	Sealed Elastomeric QWERTY
Printhead Capability	Up to 16 SoloSeries 45 PH or 8 SoloSeries 90
Printhead Interface	RS-232
Communication Ports	USB-2 port, RS-232-2 port 100 base - T Ethernet
Barcodes Supported	GTIN-12 (UPC-A), UPC-E, GTIN-13 (EAN-13), GTIN-8 (EAN-8), Code 39, GTIN-14 (UCC-128), Code 128, Data Matrix
Environment	Ambient operation temperature -40° to 104° (5°C to 40°C), Operating humidity -10 to 90%, non-condensing





SoloSeries IS

FoxJet's Bulk Ink Supply provides a larger capacity cartridge for supplying ink to multiple SoloSeries printheads. This allows longer run times in between cartridge replacement and provides cost savings on ink consumption.

Enclosure	Power-coat painted steel
Normal Operating Pressure Range	4psi to 5psi
Cable Ports	15 VDC power input supply jack; RS-232 port
Mounting	Includes bracketry for multiple mount locations
Printhead Limitations	Up to 4 bulk print ink cartridges
Electrical	15 VOC from power supply to BIS Power supply: 90 - 260 VAC, 50/60 HZ, 1.5A max
Environment	50° to 104° (10° to 40°), Operating humidity - 10 to 80% RH
Ink* <small>*Must use FJ branded ink for full functionality of the system</small>	Solo 100; 350ml cartridge porous substrates



Distributor Information



#1 Missouri Research Park Drive • St. Charles, MO 63304
800-369-5384 • www.foxjet.com • email@foxjet.com

Scan this QR Code to learn more about FoxJet's SoloSeries

