



Marksman Dro XT

High Resolution InkJet Printing









Marksman Duo XT

Dimensions:



Controller Specifications:

Touch Screen Display	7" Color Screen
Operator Interface	Graphical User Interface, WYSIWYG Editor
QWERTY Keypad	Sealed Elastomeric
Enclosure	Stainless Steel, Environmentally Sealed
Memory	128MB for unlimited message storage
Connectivity	1 – Ethernet, 2 – USB, 2 – RS232
IO Interface	IO Board Option
Auto Codes	Time, Date, Use By, Julian, Count, User Defin
	Shifts, Variable Input
Bar Codes	UPC, GTIN, I2of5, 128, Code 39, EAN, UCC,
	2D Data Matrix



Logos	Bitmap Ima
Fonts	Arial Stand
Windows PC GUI Software	Graphical L
	WYSIWYG
Dual Line Support	Yes
Direct Interface	Serial or Et

Number of Printheads

ages dard, TrueType Available User Interface, G Editor or Ethernet protocol ProSeries NP384 up to 4

Features and Benefits:



Color Touch Screen - 7" color graphical user interface guides users easily through menu functions.

Stainless Steel Enclosure provides maximum reliability in harsh environments.

User Defined

Environmentally Sealed with no moving parts on the inside eliminating the need to clean filters and provides a protected environment for the internal electronics.

Dual Production Line Support allows the Marksman Duo XT to independently control two production lines from the same user interface.

I/O Board interface card option allows for connection to external system devices for automation and control logics.

Distributor Information:





www.foxjet.com youtube.com/itwfoxjet