

# SoloSeries

## TECHNICAL DATA

### MARKSMAN HHI PLUS CONTROLLER

Touchscreen display	7" color
Operator interface	Graphical user interface, WYSIWYG editor
QWERTY keypad	Touchscreen pop-up, Unicode compatible
Encloser	Industrial thermoplastic, drop resistant
Message	512 MB for unlimited message storage
Connectivity	1 Ethernet, 1 USB, 2 RS232
Capability	Drives two independent production lines
IO interface	No
Auto codes	Time, date, count, user defined, shifts, operator input
Logos	Bitmap images, PNG, TIF, JPEG
Fonts	Arial Standard
Font sizes	1/10", 1/4" 1/2", 3/4" 1"

### PC INTERFACE

Windows PC GUI software	Graphical user interface, WYSIWYG editor
Networking software w/ database	No
Direct interface	Protocol provided

### PRINTING METHOD

Print height	Solo45: 1/2"	Solo90: 1"
Technology	FoxJet HP thermal jet	
Print resolution	300 x 300 DPI	
Standard print speeds	Up to 200 FPM	
Print speeds with reduced resolution	Up to 500 FPM	
Print options	Waterfall, top down, angled conveyer	
Print distance	Up to 1/4"	

### INK OPTIONS

Ink cartridge	Cartridge, 42ml, 45SI
Ink types	Porous and non-porous inks, water based for porous and aqueous coated cartons, enhanced solvent based option with maximized de-cap times for non-porous substrates

### SYSTEM

Regulatory listings	TUV (CE/CSA/UL)
Operating environment	50°F to 104°F

