







Continuous InkJet Printing

4900


Inkjet Technology by



Dimensions:







No

Printer Specifications:

Printhead with 2M Conduit, Standard MK7
Printhead/Conduit Options 4M, 90D
Max Lines of Print 2

Character Height Range 0.08" to 0.30"

Max Speed; Single Line Print 1230 fpm

Ink Range Dye Based

Automatic Date Codes,

Sequential NumberingYesTimed MessagesYesGraphics/Logo PrintingNo

Barcodes, Common

Linear & 2D DatamatrixNoMemory Capacity (# of Messages)50Ingress Protection RatingIP55

Base and Enclosure
Operating Temperature Range
Humidity Range (r.h., Non-Condensing)
Stainless Steel
41-113°F
90% Max

Power Supply 100-230V 50/60 Hz

Power Consumption 200W Weight 46.3-52.9 lbs

Regulatory Approvals TÜV/GS, CE Mark, FCC, RoHS

Connections / Interfacing Specifications:

Logojet PC Based Message and Logo Creation Software

and DDE Driver SoftwareOptionalRS232 PortYesEthernet OptionNoParallel I/O OptionNo

USB Port for Message and Printer Setting Back Up and Restore

Shaft Encoder, Product Detector, External Single Stage Alarm,

Volt-Free Contact Alarm Connection Yes

Features and Benefits:



- Single Button startup and shutdown.
- IP55 washdown rating is perfect for food, beverage and dairy packaging plants where washdown and harsh environments are demanding on equipment.
- Prints up to 2 lines of alpahnumerics on virtually any material due to a broad range of LINX inks.
- Production line speeds up to 1,230 feet/minute.
- Simple menu-driven interface allow for message preview for error free code creation.
- Sealed robust printhead requires no manual adjustments and removes the risk of damage to critical components.
- Self-cleaning printhead and automatic power down allows for trouble free start-ups and stops.
- Small compact design allows for quick and easy installation and mobility.
- Stainless Steel Case has no dirt traps and provides a surface which liquid naturally slides off.
- No need to stop or open the printer to refill so production is not disrupted.

Distributor Information:



