

# $Marksman_{Duo} \chi T$

High Resolution InkJet Printing









## $Marksman_{Duo} \chi T$

#### Dimensions:





### Controller Specifications:

Touch Screen Display Operator Interface QWERTY Keypad

Enclosure
Memory
Connectivity
IO Interface

IO Interface Auto Codes

**Bar Codes** 

Stainless Steel, Environmentally Sealed 128MB for unlimited message storage 1 – Ethernet, 2 – USB, 2 – RS232

> IO Board Option Time, Date, Use By, Julian, Count, User Defined

7" Color Screen

Sealed Elastomeric

Shifts, Variable Input UPC, GTIN, I2of5, 128, Code 39, EAN, UCC,

Graphical User Interface, WYSIWYG Editor

2D Data Matrix

Logos Fonts

Windows PC GUI Software

Dual Line Support Direct Interface Number of Printheads Bitmap Images

Arial Standard, TrueType Available

Graphical User Interface,

WYSIWYG Editor

Yes

Serial or Ethernet protocol ProSeries 384 up to 4 ProSeries 768 up to 2

#### Features and Benefits:



Color Touch Screen – 7" color graphical user interface guides users easily through menu functions.

Stainless Steel Enclosure provides maximum reliability in harsh environments.

**Environmentally Sealed** with no moving parts on the inside eliminating the need to clean filters and provides a protected environment for the internal electronics.

**Dual Production Line Support** allows the Marksman Duo XT to independently control two production lines from the same user interface.

**I/O Board interface card option** allows for connection to external system devices for automation and control logics.

Distributor Information:

