

FOXJET[®]
AN ITW COMPANY



LinxSeries[®] 8900

Continuous InkJet Printing

Inkjet
Technology by

LINX




Features and Benefits:



- **Easi-Change® Service Module** provides running with service intervals of up to 13,000 hours
- **Mistake-proof**, mess-free ink and solvent refill system reduces errors, downtime and the risk of using incorrect fluids
- **Automatic printhead flushing** allows you to go up to 100 starts and stops before cleaning
- **IP55-rated** with a stainless steel enclosure and no doors to open when refilling – for reliable operation even in washdown environments
- **Extended shutdowns** – up to 3 months without printer flushing or draining
- **10" Full color user interface** saves time creating and editing messages with prompted coding fields for fast editing and easy message creation

Dimensions:

Front Elevation



Side Elevation



Printhead



Printer Specifications:

Printhead with 2M Conduit, Standard	MK11
Printhead/Conduit Options	2M, 4M, 6M
Max Lines of Print	3
Character Height Range	0.07" - 0.34"
Max Speed:	
Standard Speed Single Line	478 fpm
High Performance Single Line	718 fpm
Ink Range	Dye Based
Automatic Date Codes,	
Sequential Numbering	Yes
Timed Messages	Yes
Graphics/Logo Printing	Yes, imported as bitmap files using USB port
Barcodes	ITF 2of5, Code 39, Code 128, EAN 13, EAN 8, UPCA, Pharmacode, Data Matrix, QR Code
Memory Capacity (# of Messages)	1000 using internal printer, more can be stored using USB device
Ingress Protection Rating	IP55
Base and Enclosure	Stainless Steel
Operating Temperature Range	41-113°F (32-122°F for Linx 1240 Ink Type)
Humidity Range	90% Max
Power Supply	100-230V 50/60 Hz
Power Consumption	38W (typical when printing)
Weight	53 lbs
Regulatory Approvals	GS, CE, EAC, NRTL, FCC

Connections / Interfacing Specifications:

Product Detector	Yes
RS232 Port	Optional
Dual alarm output	
(Volt free and 24v option)	Yes
Parallel I/O Option	Yes
USB and Ethernet	Yes
External single-state	
(alarm output (24v))	Yes
Shaft Encoder/	
Second Product Detector	Yes
Volt-Free Contact Alarm Connection	Yes

Distributor Information:

