

SAFETY DATA SHEET

1. Identification

Product identifier Versaprint™ V300 Black Inkjet Ink

Other means of identification

SDS number 05 Rev. P
Product code 900-0061-01
Recommended use Inkjet Ink.
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Supplier

Company Name Trident, an ITW Company **Address** 1114 Federal Road

Brookfield, CT 06804-1140

 Telephone
 1-203-740-9333

 Fax
 1-203-775-9660

 Contact person
 HSE Manager

E-mail mailto: SDS@Trident-ITW.com
Emergency telephone Infotrac 800-535-5053 (US only)
number International +1-352-323-3500

2. Hazard(s) identification

Physical hazards Not classified.

Health hazardsSerious eye damage/eye irritationCategory 2AEnvironmental hazardsHazardous to the aquatic environment, acuteCategory 3

hazard

Hazardous to the aquatic environment,

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

Precautionary statement

Prevention Wash thoroughly after handling. Wear eye/face protection. Avoid release to the environment.

Response If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Category 3

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Triethylene glycol	112-27-6	50-68
Butoxytriglycol	143-22-6	20-29.9

Versaprint™ V300 Black Inkjet Ink

SDS US

Solvent Black 29	Proprietary	5-10
Solvent Black 3	Proprietary	3-12
Non-hazardous components	Proprietary	<2.5

Composition comments

The manufacturer has claimed one or more hazardous ingredients as trade secret under the OSHA Hazard Communication Standard. The hazards of this (these) ingredient(s) are given on this SDS.

4. First-aid measures

Inhalation

If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.

Skin contact

Rinse skin with water/shower. Get medical attention if irritation develops and persists.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. Rinse mouth. If ingestion of a large amount does occur, call a poison control center immediately.

Ingestion

Most important symptoms/effects, acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Dry chemical powder. Foam. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed. Carbon oxides. Nitrogen oxides.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods
General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

This product is not flammable. Heat may cause the containers to explode.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent product from entering drains. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

7. Handling and storage

Precautions for safe handling

Avoid contact with eyes. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Use care in handling/storage.

2/6

926226 Version #: 01 Revision date: - Issue date: 13-April-2015

Storage temperature: between 4 and 49°C. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Туре	Value	Form	
Triethylene glycol (CAS	TWA	10 mg/m3	Particulate.	
112-27-6)		-		

Biological limit values

Appropriate engineering controls

No biological exposure limits noted for the ingredient(s).

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide

eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear suitable protective clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment. **Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid.
Form Liquid.
Color Black.
Odor None.
Odor threshold Not available.

pH 6 - 7

Melting point/freezing point $< 14 \, ^{\circ}\text{F} \, (< -10 \, ^{\circ}\text{C})$ Initial boiling point and boiling $> 300 \, ^{\circ}\text{F} \, (> 148.89 \, ^{\circ}\text{C})$

range

Flash point > 230.0 °F (> 110.0 °C) Pensky-Martens Closed Cup

Evaporation rate < 1 (n-butyl acetate = 1)

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density 5.5 (Air = 1) estimated

Relative density 1.09

Solubility(ies)

Solubility (water) Slightly soluble in water.

Partition coefficient Not available.

(n-octanol/water)

Versaprint™ V300 Black Inkjet Ink
SDS US

Auto-ignition temperatureNot available.Decomposition temperatureNot available.Viscosity50 - 60 cP

Other information

Percent volatile < 90 % estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Excessive heat. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents. Strong alkalis.

Hazardous decomposition Carbon oxides. Nitrogen oxides.

products

11. Toxicological information

Information on likely routes of exposure

Inhalation High mist concentrations may cause irritation of respiratory tract.

Skin contact Prolonged skin contact may cause irritation.

Eye contact Causes serious eye irritation.

Ingestion May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision.

Information on toxicological effects

Acute toxicity

 Components
 Species
 Test Results

 Butoxytriglycol (CAS 143-22-6)
 Acute

 Dermal
 LD50
 Rabbit
 3.54 ml/kg

 Oral
 LD50
 Rat
 5300 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

Versaprint™ V300 Black Inkjet Ink

SDS US

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Mobility in soil The product is slightly soluble in water. Expected to be slightly to moderately mobile in soil.

Other adverse effects None known.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to

Not established.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication **US** federal regulations

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

CERCLA Hazardous Substance List (40 CFR 302.4)

LISTED Butoxytriglycol (CAS 143-22-6)

Superfund Amendments and Reauthorization Act of 1986 (SARA) Immediate Hazard - Yes **Hazard categories**

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Chemical name CAS number % by wt. 143-22-6 20-29.9 Butoxytriglycol

Versaprint™ V300 Black Inkjet Ink SDS US 5/6

926226 Version #: 01 Revision date: -Issue date: 13-April-2015

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Butoxytriglycol (CAS 143-22-6)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Not regulated.

US. New Jersey Worker and Community Right-to-Know Act

Butoxytriglycol (CAS 143-22-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Butoxytriglycol (CAS 143-22-6) Triethylene glycol (CAS 112-27-6)

US. Rhode Island RTK

Butoxytriglycol (CAS 143-22-6)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

Issue date 13-April-2015

Revision date - 01

United States & Puerto Rico

HMIS® ratings Health: 2

Flammability: 1 Physical hazard: 0

NFPA ratings



Disclaimer Trident an ITW Company cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently

available.

Versaprint[™] V300 Black Inkjet Ink 926226 Version #: 01 Revision date: - Issue date: 13-April-2015 Yes

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).