

SAFETY DATA SHEET

1. Identification

Product identifier	TSO-4400 Black Ink		
Other means of identification	None.		
Recommended use	Printing Inks.		
Recommended restrictions	None known.		
Manufacturer/Importer/Supplier/I	Distributor information		
Company name	Foxjet, an ITW Company		
Address	1 Missouri Research Park Drive		
	St. Charles, MO 63304-5685 USA		
Telephone	800-369-5384		
E-mail	email@foxjet.com		
Contact person	Customer Service		
Emergency phone number	Emergency telephone	800-535-5053 (US only)	
		+1-352-323-3500 international	

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 2
Health hazards	Serious eye damage/eye irritation	Category 2A
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
OSHA defined hazards	Not classified.	

Label elements



	\mathbf{v}
Signal word	Danger
Hazard statement	Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness.
Precautionary statement	
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/eye protection/face protection.
Response	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. In case of fire: Use appropriate media to extinguish.
Storage	Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Methyl ethyl ketone	78-93-3	80-100

2-Pentanone		107-87-9	0-5
Ethylbenzene		100-41-4	<0.1
Other components below repo	ortable levels		11.14
Composition comments	All concentrations are in percent by weight unle percent by volume.	ess ingredient is a gas. Ga	s concentrations a
4. First-aid measures			
nhalation	Remove victim to fresh air and keep at rest in a CENTER or doctor/physician if you feel unwell.		reathing. Call a P
Skin contact	Take off immediately all contaminated clothing. attention if irritation develops and persists.	. Rinse skin with water/sho	wer. Get medical
Eye contact	Immediately flush eyes with plenty of water for present and easy to do. Continue rinsing. Get r		
ngestion	Rinse mouth. If ingestion of a large amount doe	es occur, call a poison con	trol center immed
lost important ymptoms/effects, acute and elayed	May cause drowsiness and dizziness. Headach Symptoms may include stinging, tearing, redne		
ndication of immediate medical attention and special treatment needed	Provide general supportive measures and treat immediately. While flushing, remove clothes wh ambulance. Continue flushing during transport Symptoms may be delayed.	nich do not adhere to affect	ted area. Call an
General information	Take off all contaminated clothing immediately. material(s) involved, and take precautions to pr before reuse.		
5. Fire-fighting measures			
Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemica	al powder. Carbon dioxide ((CO2).
Insuitable extinguishing nedia	Do not use water jet as an extinguisher, as this	will spread the fire.	
Specific hazards arising from he chemical	Vapors may form explosive mixtures with air. V of ignition and flash back. During fire, gases ha		
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full pro	tective clothing must be w	orn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe so without risk.	fumes. Move containers fro	om fire area if you
Specific methods	Use standard firefighting procedures and consi	der the hazards of other in	volved materials.
General fire hazards	Highly flammable liquid and vapor.		
6. Accidental release mea	sures		
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep peop ignition sources (no smoking, flares, sparks, or protective equipment and clothing during clean damaged containers or spilled material unless closed spaces before entering them. Local auth cannot be contained. For personal protection, s	flames in immediate area) -up. Avoid breathing mist of wearing appropriate protect norities should be advised	. Wear appropriate or vapor. Do not to tive clothing. Ven
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flare precautionary measures against static discharg (wood, paper, oil, etc.) away from spilled mater	ge. Use only non-sparking	tools. Keep combi
	Large Spills: Stop the flow of material, if this is possible. Cover with plastic sheet to prevent sp vermiculite, sand or earth to soak up the produc Following product recovery, flush area with wat	preading. Use a non-combu ct and place into a contain	ustible material like
	Small Spills: Absorb with earth, sand or other n	on-combustible material a	nd transfer to cont

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautionsNever return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid contact with eyes. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Use care in handling/storage.
Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре		v	alue	
2-Pentanone (CAS 107-87-9)	PEL		7	00 mg/m3	
			2	00 ppm	
Methyl ethyl ketone (CAS 78-93-3)	PEL		5	90 mg/m3	
			2	00 ppm	
US. ACGIH Threshold Lin					
Components	Туре			alue	
2-Pentanone (CAS 107-87-9)	STEL		1:	50 ppm	
Methyl ethyl ketone (CAS 78-93-3)	STEL		3	00 ppm	
	TWA		2	00 ppm	
US. NIOSH: Pocket Guide					
Components	Туре		V	alue	
2-Pentanone (CAS 107-87-9)	TWA		5	30 mg/m3	
			1	50 ppm	
Methyl ethyl ketone (CAS 78-93-3)	STEL		8	85 mg/m3	
			3	00 ppm	
	TWA		5	90 mg/m3	
			2	00 ppm	
logical limit values					
ACGIH Biological Exposu	ure Indices				
Components	Value	Determinant	Specimen	Sampling Time	
Methyl ethyl ketone (CAS 78-93-3)	2 mg/l	MEK	Urine	*	
* - For sampling details, ple	ease see the source docu	ment.			
propriate engineering htrols	changes per hour) s applicable, use proc maintain airborne lev	hould be used. V ess enclosures, vels below recon n airborne levels	Yentilation rates s local exhaust ver mended exposu to an acceptable	Good general ventilati hould be matched to c tilation, or other engine re limits. If exposure lir level. Provide eyewas	onditions. If eering controls to nits have not been
ividual protection measure	es, such as personal pro	otective equipm	ent		
Eye/face protection	Wear safety glasses				
Skin protection					

Other	Wear suitable protective clothing.
Respiratory protection	Chemical respirator with organic vapor cartridge and full facepiece.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	
Physical state	Liquid.
Form	Liquid.
Color	Black.
Odor	Characteristic.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	174.2 °F (79 °C)
Flash point	24.8 °F (-4.0 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or expl	osive limits

Explosive limit - lower (%)	1.8 % v/v
Explosive limit - upper (%)	11.5 % v/v
Vapor pressure	105 hPa (79 mm Hg)
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Partly miscible.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	0.84 g/cm3
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Strong acids.
Hazardous decomposition products	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Causes serious eye irritation.
Ingestion	May cause discomfort if swallowed.
Symptoms related to the physical, chemical and toxicological characteristics	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Information on toxicological effects

Acute toxicity	Narcotic effects.		
Components	Species	Test Results	
2-Pentanone (CAS 107-87-9)			
Acute			
Dermal			
LD50	Rabbit	6500 mg/kg	
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.		
Serious eye damage/eye irritation	Causes serious eye irrita	tion.	
Respiratory or skin sensitization	n		
Respiratory sensitization	Not a respiratory sensitiz	er.	
Skin sensitization	This product is not expected to cause skin sensitization.		
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.		
OSHA Specifically Regulat Not listed.	ed Substances (29 CFR 19	010.1001-1050)	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.		
Specific target organ toxicity - single exposure	May cause drowsiness a	nd dizziness.	
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	Not an aspiration hazard.		
Chronic effects	Prolonged inhalation may	Prolonged inhalation may be harmful.	
12. Ecological informatio	n		
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.		
Persistence and degradability	No data is available on the	ne degradability of this product.	
Bioaccumulative potential			
Partition coefficient n-octa	nol / water (log Kow)		
2-Pentanone (CAS 107-87-9)	0.91	
Methyl ethyl ketone (CAS 78		0.29	
Mobility in soil		cible with water and may spread in the aquatic environment.	
Other adverse effects	None known.		
13. Disposal consideration	ons		
Disposal instructions	Collect and reclaim or dis	spose in sealed containers at licensed waste disposal site. Dispose of	

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.

Hazardous waste code	D001: Waste Flammable material with a flash point <140 F D035: Waste Methyl ethyl ketone The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

DOT	
UN number	UN1210
UN proper shipping name	Printing ink, flammable
Transport hazard class(es)	
Class	3
Subsidiary risk	
Label(s)	3
Packing group	II
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	149, IB2, T4, TP1, TP8
Packaging exceptions	150
Packaging non bulk	173
Packaging bulk	242
ΙΑΤΑ	
UN number	UN1210
UN proper shipping name	Printing ink flammable
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	1
Environmental hazards	No.
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
IMDG	
UN number	UN1210
UN proper shipping name	PRINTING INK FLAMMABLE
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	1
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-D
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to	Not established.
Annex II of MARPOL 73/78 and	
the IBC Code	

15. Regulatory information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.	
TSCA Section 12(b) Export I	otification (40 CFR 707, Subpt. D)	
Not regulated.		
OSHA Specifically Regulate	Substances (29 CFR 1910.1001-1050)	
Not listed.		
CERCLA Hazardous Substa	ce List (40 CFR 302.4)	
2-Pentanone (CAS 107-8		
Methyl ethyl ketone (CAS	78-93-3) LISTED	

TSO-4400 Black Ink

Superfund Amendments and Rea	uthorization Act of 1986 (SAF	(A)	
Hazard categories	Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No		
SARA 302 Extremely hazardo	-		
Not listed.			
SARA 311/312 Hazardous chemical	Yes		
SARA 313 (TRI reporting) Not regulated.			
Other federal regulations			
Clean Air Act (CAA) Section	112 Hazardous Air Pollutants	(HAPs) List	
Not regulated. Clean Air Act (CAA) Section	112(r) Accidental Release Pre	vention (40 CFR 68.130)	
Not regulated. Safe Drinking Water Act	Not regulated.		
(SDWA)	not rogulatou.		
Drug Enforcement Admir Chemical Code Number	nistration (DEA). List 2, Esser	ntial Chemicals (21 CFR 1310.02(b) and 1	310.04(f)(2) and
Methyl ethyl ketone (C Drug Enforcement Admir		6714 empt Chemical Mixtures (21 CFR 1310.1	2(c))
Methyl ethyl ketone (C DEA Exempt Chemical M	CAS 78-93-3)	35 %WV	
Methyl ethyl ketone (C		6714	
US state regulations	10 10-33-37		
US. Massachusetts RTK - Sul	hstanco l ist		
2-Pentanone (CAS 107-87 Methyl ethyl ketone (CAS 1 US. New Jersey Worker and (-9) 78-93-3)	t	
Methyl ethyl ketone (CAS 3 US. Pennsylvania Worker and	,	Law	
2-Pentanone (CAS 107-87 Methyl ethyl ketone (CAS 7 US. Rhode Island RTK	-9)		
Methyl ethyl ketone (CAS	78-93-3)		
US. California Proposition 65 WARNING: This product o		e State of California to cause cancer.	
US - California Propositio	on 65 - Carcinogens & Reproc	ductive Toxicity (CRT): Listed substance	
Ethylbenzene (CAS 10	00-41-4)		
International Inventories			
Country(s) or region	Inventory name		On inventory (yes/no)*
Australia	Australian Inventory of Chemic	al Substances (AICS)	No
Canada	Domestic Substances List (DS	L)	No
Canada	Non-Domestic Substances List	t (NDSL)	Yes
China	Inventory of Existing Chemical	Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Substances (EINECS)	Commercial Chemical	No
Europe	European List of Notified Chen	nical Substances (ELINCS)	No
Japan	Inventory of Existing and New	Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)		No
New Zealand	New Zealand Inventory		No
Philippines	Philippine Inventory of Chemic (PICCS)	als and Chemical Substances	No

Country(s) or region

Inventory name

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	07-July-2015
Revision date	-
Version #	01
HMIS® ratings	Health: 2 Flammability: 3 Physical hazard: 0
NFPA ratings	2 0

Disclaimer

Diagraph Marking and Coding Division, an ITW Company cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.